

PT-306 Pressure Transmitter

Product description:

PT-306 pressure transmitter adopts imported sensor core, stainless steel isolation type small structure, compact appearance, easy to install. With a wide range and a variety of output signals, this product has good stability in a wide range of temperature, widely used in refrigeration, air conditioning equipment and air compressor and other fields. With CE certification, it can directly replace a variety of similar imported products, such as Atlas, MSI, HUBA. And it can be customized according to user needs product shape and process connection mode. There are a variety of different specifications to choose, it also can be OEM OEM manufacturing requirements.




Main features:

- A variety of pressure range and electrical output;
- Compact structure, aviation plug connection is more convenient and reliable;
- Ultra-stable technology;
- High frequency dynamic response;
- Suitable for high temperature environment;
- Good long-term stability.


Technical specifications:

Pressure range	0MPa~0.1MPa~4MPa
Output signal	0.5~4.5VDC, 4~20mA
Overload pressure	200%FS
Supply voltage	3~5VDC, 24VDC (10-36VDC)
Process connection	G1/4, R1/4etc, can be customized
Accuracy	±0.5%FS、±1%FS
Operating temperature	-40℃~85℃
Temperature drift	±0.03%FS/℃
Protection	IP65
Electrical connection	aviation plug

Dimensions (thread can be customized):



Electrical connection:



	4~20mA	0~5VDC, 0.5~4.5VDC
Red	Power supply+	Power supply+
Black	Output	Power supply-
Green or White	N/A	Output